

UN | UX Series | Video Wall Displays

MultiSync® Model	Size inch/cm	Brightness in cd/m²	Haze Level¹	Orientation²	Input	
UN462A 2,3	46 / 117	700	P	L, P	HDMI In/Out, DP In/Out, DVI-D, VGA	
UN462VA 2,3	46 / 117	500	P	L, P		
UN492S 1,3	49 / 123	700	P	L, P		
UN492VS 1,3	49 / 123	500	P	L, P		
UN552A 2,3	55 / 140	700	P	L, P		
UN552 1,3	55 / 140	700	P	L, P		
UN552V 1,3	55 / 140	500	P	L, P		
UN552S 1,3	55 / 140	700	P	L, P		
UN552VS 1,3	55 / 140	500	P	L, P		
X554UNS-2 2	55 / 140	700	P	L, P		DVI-D, HDMI, DP In/Out, VGA
X554UNV-2 2	55 / 140	500	P	L, P		
X555UNS 1	55 / 140	700	P	L, P		
UN551S 1	55 / 140	700	P	L, P		
UN551VS 1	55 / 140	500	P	L, P		
UX552 2,3	55 / 140	700	P	L, P	HDMI In/Out, DP In/Out, DVI-D, VGA	
UX552S 2,3	55 / 140	700	P	L, P		

Panel Technology IPS¹ or PVA²



- Enhanced imaging performance via the SpectraView™ engine
- Easy set-up with Auto TileMatrix
- Secure reliability and longevity
- UX Series supports connection of additional power supply for redundancy



XHB Series | High Brightness

MultiSync® Model	Size inch/cm	Brightness in cd/m²	Haze Level*	Orientation**	Input
X554HB	55 / 140	2700	S	L, P	HDMI, DP In/Out, DVI-D, VGA
X754HB	75 / 191	2500	S	L, P	



- Programmable Ambient Light Sensor
- Sunlight-proof operation
- Automated thermal management



BT Series | Stretched Display

MultiSync® Model	Size inch/cm	Brightness in cd/m²	Haze Level*	Orientation**	Input
BT421	42 / 107	700	Pro (44)	L, P	DVI: 2 In, 1 Out, LAN



- Space efficient display solution with ultra-wide screen ratio of 16:4

NaViSet Administrator 2

Unified remote management software for NEC desktop monitors, large format displays and projectors.

SpectraView Engine

Advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.

Open Modular Intelligence (OMi)

Future ready expansion to upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute module 3 or signal interfaces for content feed and computing.


Customisable Displays

Guaranteed reliability even under the toughest conditions is achieved with robust protective glass designed to withstand external impacts. Available for NEC MultiSync® C / V / P / UN Series.

NEC MultiSync® P Series displays can be transformed into highly attractive and engaging devices with semi-transparent mirror glass. Colour match NEC MultiSync® V and P Series displays to suit their environment with coloured bezels in any colour of the RAL range.

Document Name: Large Format Displays Pocket Guide
 Document Revision: Edition 5, 2019
 Document Date: 09/19
 Created by: FG

For more information visit us at www.nec-display-solutions.com



NEC Display Solutions

Large Format Displays

Orchestrating a brighter world **NEC**

E Series | Entry Level Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
E327	32 / 81	350	S	L	3 HDMI, VGA
E437Q ¹	43 / 109	350	S	L	3 HDMI, VGA
E507Q ¹	50 / 127	350	S	L	3 HDMI, VGA
E557Q ¹	55 / 140	350	S	L	3 HDMI, VGA
E657Q ¹	65 / 165	350	S	L	3 HDMI, VGA



- Slim design and integrated speakers
- Future-ready connectivity
- Standalone operation



C Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
C431	43 / 109	400	P	L, P, FU	3 HDMI, DP, VGA
C501	50 / 127	400	P	L, P, FU	3 HDMI, DP, VGA
C551	55 / 140	400	P	L, P, FU	3 HDMI, DP, VGA
C651Q ¹	65 / 165	350	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
C751Q ¹	75 / 189	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
C861Q ¹	86 / 217	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
C981Q ¹	98 / 248	350	P	L, P	3 HDMI, DP: 2 In, 1 Out



- Integrated Media Player
- Slim profile and modern design for seamless integration
- Low reflective panel and “pixel-free” viewing experience for excellent readability¹
- ShadowSense™ touch models available



V Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
V323-3	32 / 81	450	S	L, P	HDMI, DP, DVI-D In/Out, VGA
V404 ²	40 / 102	500	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
V484 ²	48 / 122	500	P	L, P, FU, FD	
V554 ²	55 / 140	500	P	L, P, FU, FD	3 HDMI, DP: 2 In, 1 Out
V554Q ^{1,2}	55 / 140	500	P	L, P	
V654Q ^{1,2}	65 / 165	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V754Q ^{1,2}	75 / 189	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V864Q ^{1,2}	86 / 217	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V984Q ^{1,2}	98 / 248	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out



- Open Modular Intelligence for scalable computing power
- Reliable colour reproduction
- “Pixel-free” viewing experience¹
- 3M™ PCAP touch models available



P Series | Professional Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
P404	40 / 102	700	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
P484	48 / 122	700	P	L, P, FU, FD	
P554	55 / 140	700	P	L, P, FU, FD	
P654Q ¹	65 / 165	700	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
P754Q ¹	75 / 189	650	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out



- Open Modular Intelligence for scalable computing power
- Superb readability in bright light environments
- Long-term operation in demanding environments
- ShadowSense™ touch models available



CB Series | Entry Level Collaboration

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Touch Technology	Orientation**	Front USB
CB651Q	65 / 164	350	Infrared	L	2
CB751Q	75 / 189	350	Infrared	L	2
CB861Q	86 / 217	350	Infrared	L	2



- Simple operation with front access to major functionalities
- Easy installation with included wallmount
- Instant start-up with built-in whiteboard and wireless screen sharing



NEC InfinityBoards | Collaboration Solutions

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Touch Technology	Orientation**	USB Hubs
55" InfinityBoard ¹	55 / 140	500	InGlass™	L, P, FU	4x USB 3
65" InfinityBoard	65 / 165	500	InGlass™	L, P, FU	4x USB 3
75" InfinityBoard	75 / 191	500	InGlass™	L, P, FU	4x USB 3
86" InfinityBoard	86 / 217	500	InGlass™	L, P, FU	4x USB 3

¹ only 2.1 model



- Create, collaborate, communicate
- Natural writing experience
- Simplified video conferencing
- 2.0 models with Huddly GO camera
- 2.1 models with Huddly IQ camera

